



东莞中力仪器科技有限公司

Dongguan Zhongli Instrument Technology Co., Ltd

Tel: +86-769-33657986

Fax: +86-769-33657987

Website: www.zltester.com

E-mail: Zhongli@zltester.com

Add: No.62, Xinhe Management of Area, Wanjiang District, Dongguan, Guangdong, China

Introduction

Name: ZL-6001B Economic type salt spray testing machine (Button operation)



→Direct Manufacturer.

→ Excellent Quality.

→Technical Innovation.

→ Fast Shipping.

→Superior Service.



东莞中力仪器科技有限公司

Dongguan Zhongli Instrument Technology Co., Ltd

Tel: +86-769-33657986

Fax: +86-769-33657987

Website: www.zltester.com

E-mail: Zhongli@zltester.com

Add: No.62, Xinhe Management of Area, Wanjiang District, Dongguan, Guangdong, China

Equipment summary:

Salt spray testing machine used to test the corrosive resistance of products whose the surface was treated with paint, electroplating, inorganic and organic film, anode handling, anti-rust oil, etc.

corresponding standard :

- 1.GB/T 2423.17-1993 salt spray test
- 2.GB/T 2423.18-2000 salt spray test
- 3.GB/T 10125-1997 salt spray test
- 4.ASTM.B117-97 salt spray test
- 5.JIS H8502 salt spray test
- 6.IEC68-2-11 salt spray test
- 7.IEC68-2-52 1996 salt spray test
- 8.GB.10587-89 salt spray test
- 9.CNS.4158 salt spray test
- 10.CNS.4159 CASS Accelerated acetic acid copper salt spray test
- 11..GB/T 12967.3-91 CASS Accelerated acetic acid copper salt spray test

Technical parameters:

Model	ZL-6001B (108L)	ZL-6001B (270L)	ZL-6001B (600L)
Inside box size(cm)	60x45x40	90x60x50	160x100x50
Outside box size(cm)	107x60x118	141x88x128	210x130x140
Testing room temperature	Salt test (NSS ACSS)35°C±1°C/ Corrosion Test (CASS)50°C±1°C		
Pressure barrel temperature	Salt test (NSS ACSS)47°C±1°C/ Corrosion Test (CASS)63°C±1°C		
Brine temperature	35°C±1°C 50°C±1°C		
Testing room Capacity	108L	270L	600L



东莞中力仪器科技有限公司

Dongguan Zhongli Instrument Technology Co., Ltd

Tel: +86-769-33657986

Fax: +86-769-33657987

Website: www.zltester.com

E-mail: Zhongli@zltester.com

Add: No.62, Xinhe Management of Area, Wanjiang District, Dongguan, Guangdong, China

Brine tank capacity	15L	25L	50L
Salt concentration	The concentration of sodium chloride 5% or the 5% concentration of sodium chloride add 0.26g per liter of copper chloride (CuCl ₂ 2H ₂ O)		
Air pressure	1.00±0.01kgf/cm ²		
Spray volume	1.0~2.0ml/80cm ² /h (working at least 16 hours, and then take the average)		
Testing room relative humidity	85% above		
PH	6.5~7.2 3.0~3.2		
Spray form	Programmable spray (Including continuous and intermittent spray)		
Power	AC220V1Φ10A	AC220V1Φ15A	AC220V1Φ20A

Machine detailed picture :





东莞中力仪器科技有限公司

Dongguan Zhongli Instrument Technology Co., Ltd

Tel: [+86-769-33657986](tel:+86-769-33657986)

Fax: [+86-769-33657987](tel:+86-769-33657987)

Website: www.zltester.com

E-mail: Zhongli@zltester.com

Add: No.62, Xinhe Management of Area, Wanjiang District, Dongguan, Guangdong, China

